

424-00  
FISH & RICHARDSON P.C.,P.A.

3300 Dain Rauscher Plaza  
60 South Sixth Street  
Minneapolis, Minnesota  
55402

Telephone  
612 335-5070

Facsimile  
612 288-9696

Web Site  
www.fr.com

April 3, 2000

Attorney Docket No.: 10225-023001

**Box Patent Application**

Assistant Commissioner for Patents  
Washington, DC 20231

Presented for filing is a new original patent application of:

Applicant: JOSE DE LA TORRE-BUENO

Title: REMOTE INTERPRETATION OF MEDICAL IMAGES

Enclosed are the following papers, including those required to receive a filing date under 37 CFR 1.53(b):

	Pages
Specification	7
Claims	5
Abstract	1
Declaration	[To be Filed at a Later Date]
Drawing(s)	3

Enclosures:

— Postcard.

This application is entitled to small entity status. A small entity statement will be filed at a later date.

Basic filing fee	\$345
Total claims in excess of 20 times \$9	\$90
Independent claims in excess of 3 times \$39	\$117
Fee for multiple dependent claims	\$0

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL454377604US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

April 3, 2000  
Date of Deposit

Signature

Vince Defante  
Typed or Printed Name of Person Signing Certificate

BOSTON

DELAWARE

NEW YORK

SAN DIEGO

SILICON VALLEY

TWIN CITIES

WASHINGTON, DC

FISH & RICHARDSON P.C., P.A.

Assistant Commissioner for Patents  
April 3, 2000  
Page 2

Total filing fee: \$552

Under 37 CFR §1.53(d), no filing fee is being paid at this time.

If this application is found to be incomplete, or if a telephone conference would otherwise be helpful, please call the undersigned at (612) 335-5070.

Kindly acknowledge receipt of this application by returning the enclosed postcard.

Please send all correspondence to:

KENT J. SIEFFERT  
Fish & Richardson P.C., P.A.  
60 South Sixth Street, Suite 3300  
Minneapolis, MN 55402

Respectfully submitted,

A handwritten signature in black ink, appearing to read "Kent J. Sieffert", with a long horizontal flourish extending to the right.

Kent J. Sieffert  
Reg. No. 41,312  
Enclosures  
KJS/tja  
60010148.doc

APPLICATION  
FOR  
UNITED STATES LETTERS PATENT

TITLE: REMOTE INTERPRETATION OF MEDICAL IMAGES


APPLICANT: Jose de la Torre-Bueno

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL454377604US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit April 3, 2000

Signature 

Vince Defante  
Typed or Printed Name of Person Signing Certificate

## REMOTE INTERPRETATION OF MEDICAL IMAGES

### BACKGROUND

Pathologists typically use microscopes when diagnosing physiological conditions such as cancer, infectious disease and prenatal disorders. Typically, tissue samples on a slide  
5 are loaded onto the microscope, the microscope objective or lens focuses on an area of the sample, and the sample is scanned for particular features or objects of interest. In this manner, the microscope helps the pathologist to visually determine the presence of abnormal numbers or types of cells, organelles, organisms or biological markers.

Recently, automated microscopes have been integrated into medical imaging systems  
10 that include a variety of networked components. The medical imaging system provides an environment for storing and retrieving the medical images produced by the microscopes. The components of the medical imaging system are spread throughout the department or hospital, or even located remotely, and connected by a communication network.

An image acquisition device is coupled to the microscope and captures images  
15 produced by the microscope. The image acquisition device can include a variety of components. For example, the image acquisition device can include a video camera coupled to a high-speed frame grabber for capturing the stream of video produced by the video camera and generating a series of digital images. Alternatively, the electronic camera can be a megapixel digital camera. The microscope and the image acquisition device can acquire  
20 images for a number of different color planes and at several different focal planes. These images can be stitched together to form a two-dimensional or three-dimensional composite image. As a result of the combination, and because the images are typically in color and at high-resolution, the composite images place significant storage and bandwidth requirements on the medical imaging system. For example, a composite image for a single tissue slide can  
25 often exceed a gigabyte in size.

Image storage and archival devices provide a central library for storing the medical images captured by the image acquisition device. Image storage devices include one or more databases and image servers for fast access to recently acquired images. Archival devices, such as optical disc jukeboxes and tape backup systems, provide long-term storage. When a

pathologist wishes to view an archived image, the image is automatically “migrated” from the corresponding archival device to one of the image storage devices.

Diagnostic quality view stations display the images captured by the image acquisition system. In order to assist the pathologist in interpreting a medical image, a view station is able to perform a variety of image processing operations on the medical image. For example, the pathologist at the view stations may invoke algorithms to perform densitometry on selected regions of the medical image in order to identify concentration of a particular analyte within the tissue sample. Other image processing operations are useful for finding objects within the image such as the nuclei of the cells, computing an integrated optical density for the nuclei of the cells and reporting the number of molecules per cell. Most image processing operations output a fixed number (score), often falling within a predetermined range.

## SUMMARY OF THE INVENTION

In general, the invention facilitates the remote interpretation of medical images. In order to facilitate the timely diagnosis of a tissue sample, it is desirable that a medical professional, such as a pathologist, be able to remotely view and interpret a medical image. The immense size of a medical image for a single tissue sample typically makes remote viewing unworkable due to bandwidth constraints. Compression algorithms can produce an image suitable for transmission, but the data lost during compression can lead to inaccurate results from the image analysis operations.

According to one aspect, the invention is directed to a system in which a remote view station is communicatively coupled to an image server and receives a compressed version of a source medical image. The remote view station uncompresses and displays the received medical image. The remote view station selects a region of the displayed medical image as a function of input received from a medical professional, such as a pathologist. Based on the input, the remote view station transmits region information, such as a series of pixel coordinates, back to the image server. The image server applies image analysis operations to a region of the source medical image that corresponds to the selected region of the compressed medical image. In this manner, the data loss that occurs during image compression does not effect the image analysis operations. As such, the image analysis

operations produce more accurate results than if the operations were applied by the remote view station on the compressed image.

In another aspect, the invention is directed to a method for remotely interpreting medical images. According to the method, a compressed medical image is generated from a source medical image and transmitted from an image server to a remote view station for display. In one implementation, the compressed medical image is transmitted over a global packet-switched network such as the Internet. A region of the medical image displayed by the remote view station is selected in response to input from a medical professional. Region information, defining the selected region of the displayed medial image, is transmitted from the remote view station back to the image server. Based on the region information, image analysis operations are applied to a corresponding region of the source medical image. A resulting score is communicated to the remote view station for display. A diagnosis is received from the remote view station and associated with the source medical image in a database maintained by the image server.

Various embodiments of the invention are set forth in the accompanying drawings and the description below. Other features and advantages of the invention will become apparent from the description, the drawings, and the claims.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram providing a high-level illustration of the various components of the invention.

FIG. 2 is a flowchart illustrating one embodiment of a process for remotely interpreting medical images.

FIG. 3 is a block diagram illustrates one embodiment of a computer suitable for implementing the various embodiments of the invention.

## DETAILED DESCRIPTION

Figure 1 is a block diagram illustrating a system 10 that facilitates remotely viewing and interpreting medical images. System 10 includes remote view station 26 this is communicatively coupled to medical imaging system (MIS) 12 by network 20, which

represents any packet-switched network such as a local area network or the Internet. MIS 12 includes image acquisition devices 14 that represent any medical imaging device that generates digital medical images, such as an electronic camera used in conjunction with an automated microscope. Other image acquisition devices include computed tomography (CT), nuclear medicine, magnetic resonance imaging (MRI), ultrasound and X-ray devices. Image server 24 stores the images that are generated by image acquisition device 14 and, upon request, communicates the images to view stations 16 for display. Using view stations 16, a medical professional, such as a pathologist, can perform a variety of image processing techniques on selected regions to assist in rendering a diagnosis.

As described in detail below, image server 24 of MIS 12 communicates compressed medical images to remote view station 26 for interpretation by a medical professional. Using a network software application, such as a web browser, the medical professional interacts with remote view station 26 to select various regions of interest within the image. Based on the selection, image server 24 applies image analysis functions directly to the source medical image stored on image server 24, thereby generating a more accurate score than if applied by remote view station 26 to the medical image after compression. The resultant score produced by the image processing operations is communicated to remote view station 26 to assist the medical professional in interpreting the medical image and rendering a diagnosis.

Figure 2 is a flow chart illustrating one implementation of a process 28 that facilitates the interpretation of medical images via remote view station 26. Using a network software application the medical professional interacts with remote view station 26, accesses MIS 12 and receives a list of cases that are marked for review, i.e., cases in which images have been acquired by image acquisition devices 14 but have not been reviewed by a medical professional (30). Upon reviewing the list displayed by remote view station 26, the medical professional selects one of the cases for review (32).

Based on the selection, image server 24 compresses medical images associated with the case and communicates the compressed images to remote view station 26 via network 20 (34). Remote view station 26 decompresses the images and displays the uncompressed images for review by the medical professional (36). The displayed image is not a pixel-by-pixel duplicate of the original source image stored on image server 24 because of data loss during compression. Several algorithms, however, are known that can achieve a compression ratio, such that the compressed image uses relatively low bandwidth, without

significantly changing the visual representation of the image. Therefore, compressing the image can be effectively lossless with respect to human vision. For example, it has been found that both JPEG compression and fractal image compression, when set for to moderate compression, result in images suitable for transmission without resulting in data loss

5 perceptible with human vision.

Using a pointing device, such as a light pen, mouse or track ball, the medical professional selects one or more regions of interest. The medical professional can tag a region for image processing or can request that image server 24 transmit image data for the selected region using a lower compression setting. For example, the medical professional  
10 can direct image server 24 to transmit an image using low compression or even to transmit an uncompressed pixel-by-pixel duplicate of the selected region. Remote view station 26 encodes the shape and size of the selected region and transmits the region information to MIS 12 by network 20 (38). The region information defines the boundaries of the selected regions and, in one implementation, is a set of pixel coordinates defining the outlines of the selected  
15 regions. As such, the region information typically comprises a small amount information and can be quickly transmitted to image server 24.

If the medical professional requests that image server 24 transmit image data for a region of interest using a lower compression setting, or no compression, then image server 24 extracts the corresponding pixel data from the source image and communicates the pixel data  
20 to remote view station 26 (40). In this fashion, the medical professional can view regions of interest at higher resolution, or even a pixel-per-pixel duplicate, without requiring that image server 24 transmit the entire source image across network 20. Upon viewing the region of interest, the medical professional can tag the region for image processing or can select sub-regions of interest.

25 If the medical professional tags a selected region for image processing, image server 24 executes the requested image processing operation on the corresponding source medical image (42). More specifically, image server 24 analyzes the region information received from remote view station 26 and applies the image processing operation to a subset of the pixel data of the source image. The subset pixel data is selected based on the boundaries  
30 defined by the region information received from remote view station 26. In this manner, the image processing operation produces a more accurate score than if the operation were applied by remote view station 26 to the image that has been compressed for transmission



and then uncompressed for display at the remote view station. As such, the data loss that occurs during compression does not effect the image analysis.

Image server 24 communicates the scores for each region to remote view station 26 for display to the medical professional (44). Based on the visual display of the medical image as well as the scores associated with regions of interest, the medical professional interprets the medical image and renders a diagnosis. For example, the medical professional may determine that a particular tissue sample is cancerous. Remote view station 26 communicates the diagnosis to MIS 12 for association with the appropriate case within a database maintained by image server 24 (46).

The invention can be implemented in digital electronic circuitry, or in computer hardware, firmware, software, or in combinations thereof. Furthermore, the invention can be implemented in one or more computer programs that are executable within an operating environment of a programmable system embodied and tangibly stored in a machine-readable storage device.

Figure 3 illustrates an example of a computer 100 suitable for use as view station 26 in order to implement or perform various embodiments of the invention. As shown in Figure 3, the computer 100 includes a processor 112 that in one embodiment belongs to the PENTIUM® family of microprocessors manufactured by the Intel Corporation of Santa Clara, California. However, computer 100 can be implemented on computers based upon other microprocessors, such as the MIPS® family of microprocessors from the Silicon Graphics Corporation, the POWERPC® family of microprocessors from both the Motorola Corporation and the IBM Corporation, the PRECISION ARCHITECTURE® family of microprocessors from the Hewlett-Packard Company, the SPARC® family of microprocessors from the Sun Microsystems Corporation, or the ALPHA® family of microprocessors from the Compaq Computer Corporation.

Computer 100 includes system memory 113, including read only memory (ROM) 114 and random access memory (RAM) 115, which is connected to the processor 112 by a system data/address bus 116. ROM 114 represents any device that is primarily read-only including electrically erasable programmable read-only memory (EEPROM), flash memory, etc. RAM 115 represents any random access memory such as Synchronous Dynamic Random Access Memory.

Within the computer 100, input/output bus 118 is connected to the data/address bus 116 via bus controller 119. In one embodiment, input/output bus 118 is implemented as a standard Peripheral Component Interconnect (PCI) bus. The bus controller 119 examines all signals from the processor 112 to route the signals to the appropriate bus. Signals between the processor 112 and the system memory 113 are merely passed through the bus controller 119. However, signals from the processor 112 intended for devices other than system memory 113 are routed onto the input/output bus 118.

Various devices are connected to the input/output bus 118 including hard disk drive 120, floppy drive 121 that is used to read floppy disk 151, and optical drive 122, such as a CD-ROM drive that is used to read an optical disk 152. The video display 124 or other kind of display device is connected to the input/output bus 118 via a video adapter 125 and preferably is a high-resolution display suitable for viewing medical images. Computer 100 also includes a modem 129 and network interface 53 for communicating over network 20 via either a wired or wireless connection.

A medical professional enter commands and information into the computer 100 by using a keyboard 140 and/or pointing device, such as a mouse 142, which are connected to bus 118 via input/output ports 128. Other types of pointing devices (not shown in Figure 1) include track pads, track balls, joysticks, data gloves, head trackers, and other devices suitable for positioning a cursor on the video display 124.

Software applications 136 and data are typically stored via one of the memory storage devices, which may include the hard disk 120, floppy disk 151, CD-ROM 152 and are copied to RAM 115 for execution. Operating system 135 executes software applications 136 and carries out instructions issued by the user. The Basic Input/Output System (BIOS) 117 for the computer 100 is stored in ROM 114 and is loaded into RAM 115 upon booting. BIOS 117 is a set of basic executable routines that help transfer information between the computing resources within the computer 100.

This application is intended to cover any adaptation or variation of the present invention. It is intended that this invention be limited only by the claims and equivalents thereof.

What is claimed is:

1. A method comprising:

generating a compressed medical image from a source medical image;  
transmitting the compressed medical image to a remote view station for  
5 display;

selecting a region of the displayed medical image; and

applying image analysis operations to a region of the source medical image  
corresponding to the selected region of the compressed medical image.

10 2. The method of claim 1 wherein transmitting the compressed medical image includes  
transmitting the compressed medical image over a global packet-switched network.

3. The method of claim 1 and further including transmitting region information from the  
remote view station to an image server, wherein the region information defines the  
15 selected region of the displayed medial image.

4. The method of claim 3, wherein the region information is a series of pixel  
coordinates.

20 5. The method of claim 1, wherein applying the image analysis operations includes  
outputting a score and communicating the score to the remote view station for  
display.

6. The method of claim 1 and further including receiving a diagnosis from the remote  
25 view station and associating the diagnosis with the source medical image in a  
database.

7. The method of claim 1, wherein selecting the region of the compressed medical  
image includes receiving input from a pointing device controlled by a user to outline  
30 the region of the compressed medical image.

8. The method of claim 1, wherein generating a compressed medical image includes applying a compression algorithm that reduces data losses that are detectable with human vision.

5 9. The method of claim 8, wherein generating a compressed medical image includes applying a JPEG compression algorithm.

10. A system comprising

an image server storing a source medical image;

10 a remote view station communicatively coupled to the image server to receive a compressed version of the source medical image, wherein the remote view station includes an input device for selecting a region of the compressed medical image, and further wherein the image server applies an image analysis operation on a region of the source medical image that corresponds to the selected region of the compressed medical image.

15

11. The system of claim 10, wherein the remote view station transmits region information from the remote view station to the image server, wherein the region information includes a plurality of pixel coordinates outlining the selected region of the compressed image.

20

12. The system of claim 10, wherein the image server applies the image analysis operations to generate a score and communicates the score to the remote view station for display.

25

13. The system of claim 10, wherein the image server includes a database associating a diagnosis received from the remote view station with the source medical image.

30 14. The system of claim 10, wherein the remote view station includes a pointing device controllable by a user to outline the region of the compressed medical image.

15. A computer program, tangibly stored on a computer-readable medium, comprising instructions operable to cause a programmable processor to:

generate a compressed medical image from a source medical image;

transmit the compressed medical image to a remote view station for display;

receive region information from the remote view station, wherein the region information defines a region within the compressed medical image; and

apply image analysis operations to a region of the source medical image as a function of the region information.

16. The computer program of claim 15 and further including instructions to cause the processor to transmit the compressed medical image over a global packet-switched network.

17. The computer program of claim 15 wherein the region information is a series of pixel coordinates.

18. The computer program of claim 15 and further including instructions to cause the processor to output a score and communicating the score to the remote view station for display

19. The computer program of claim 15 and further including instructions to receive a diagnosis from the remote view station and associate the diagnosis with the source medical image in a database.

20. The computer program of claim 15 and further including instructions to apply a compression algorithm that reduces data losses that are detectable with human vision.

21. A computer-readable medium having a data structure stored thereon comprising:

a data field identifying a source medical image;

a data field identifying a compressed version of the source medical image; and

a data field storing an output score from an image analysis operation applied to a region of the source medical image.

22. The computer-readable medium of claim 21, wherein the data structure includes a data field associating a diagnosis with the source the medical image.

5 23. A method comprising:

compressing a source medical image at a compression level;

transmitting the compressed medical image to a remote view station for display;

10 receiving region information from the remote view station, wherein the region information defines a region of the compressed medical image; and

compressing a region of the source medical image at a second compression level as a function of the region information.

15 24. The method of claim 22 wherein transmitting the compressed medical image includes transmitting the compressed medical image over a global packet-switched network.

25. The method of claim 23, wherein the region information is a series of pixel coordinates.

20 26. The method of claim 23 and further including receiving a diagnosis from the remote view station and associating the diagnosis with the source medical image in a database.

25 27. A method comprising:  
transmitting a medical image to a remote view station for display;  
receiving region information from the remote view station, wherein the region information defines a region of the displayed medical image; and  
locally applying an image processing operation at the image server to a region of the source medical image as a function of the region information.


30 28. The method of claim 27 wherein transmitting the medical image includes transmitting the medical image over a global packet-switched network.


- [illegible]

## ABSTRACT OF THE DISCLOSURE

[illegible]





[illegible]




FIG. 3 is a block diagram of a computer system 100.